

Amendment to the claims:

1. (currently amended) A display comprising: an electrically insulative substrate; a plural of current driven type light emitting elements arranged, on the electrically insulative substrate, in a matrix form; a scanning line which is disposed at least one piece per each element row; a data line which is disposed at least one p per one or two element columns; a power source supply line disposed on the electrically insulative substrate; and a switching circuit portion which is disposed at least one piece per at least one current driven type light emitting element, and can control electrical conduction between at least one of the current driven type light emitting element and the power source supply line according to a pixel selecting signal supplied to the scanning line and to a pixel signal supplied to the data line, wherein the switching circuit portion includes a plurality of switching elements, wherein the each current driven type light emitting element comprises; a first electrode layer disposed on the surface of a protective layer formed on the electrically insulative substrate; a light emitting portion laminated on the first electrode layer; and a second electrode layer formed on the light emitting portion; and wherein the power source supply line is buried within the protective layer.

2. (currently amended) The display according to claim 1, wherein the power source supply line is provided within a through-hole which is formed so as to pass through the protective Layer from lower surface to upper surface.

3. (currently amended) The display according to claim 1, wherein the power source supply line is provided so as an upper surface of the protective layer and an upper surface of the power source supply line are ~~made~~ flush with each other.

4. (previously presented) The display according to claim 1 wherein an insulating layer is provided so as to cover the upper surface of the power source supply line.

5. (previously presented) The display according to claim 1, wherein the current driven type light emitting element is an electroluminescent element.

6 (previously presented) An electronic device comprising the display according to claim 1.

7. (currently amended) A method for manufacturing a display, comprising:

~~a process of~~ forming a switching circuit portion on an electrically insulative substrate;

~~a process of~~ forming a protective layer, on the electrically insulative substrate with the switching circuit portion, so as to cover the switching circuit portion;

~~a process of~~ forming a through—hole in the protective layer so as to pass through the protective layer from a upper surface to a lower surface at a region which a power source supply line of the switching circuit portion is disposed;

~~a process of~~ forming the power source supply line so as to fill the through—hole; and

~~a process of~~ forming an insulating layer so as to cover the upper surface of the power source supply line disposed within the protective layer.

8. (previously presented) The method for manufacturing a display according to claim 7, wherein the power source supply line is formed by a plating method.